

MUELLER

R-2361 RESILIENT WEDGE GATE VALVE

OS&Y: 2" – 12"/DN50 – DN300 Groove x Groove/Flange x Groove ends



PRODUCT FEATURES

- Outside Screw & Yoke (OS&Y) Gate Valve.
- UL 262 Listed and FM 1120/1130 Approved and certified to ANSI/NSF 61 & 372.
- Iron body with Mueller® PRO-GARD® Fusion Bonded Epoxy Coated interior and exterior surfaces.
- Adjustable packing.
- Rubber encapsulated iron wedge.
- Handwheel – open left or open right.
- 350psig (2400kPa/24barg) maximum working pressure – 700psig (4800kPa/48barg) static test.
- Epoxy coating meets or exceeds all applicable requirements ANSI/AWWA C550.
- Meets or exceeds all applicable requirements of ANSI/AWWA C515.
- Groove ends comply with AWWA C606.
- Groove ends fit steel IPS pipe.
- Flange end drilling complies with ASME/ANSI B16.1 class 125 and B16.42 class 150

OPTIONS

- Stainless Steel stems: Type 304, 316, or 431.
- Low zinc, silicon Bronze ASTM B98-C66100/H02 stem.
- EPDM disc and O-rings
- PN10/PN16 drilling (Flange X Groove End Valves ONLY).

*Per ANSI/AWWA C111, working pressure above 250 psi requires the use of a special gasket rated for the higher pressure.


PARTS LIST

ID	PART NAME	MATERIAL
1	Cap Nut	Bronze ASTM B62
2	Handwheel	Ductile Iron ASTM A536 (See Note 1)
3	Washer	Brass ASTM B36
4	Bush Nut	Bronze ASTM B62
5	Gland Nut	Bronze ASTM B98
6	Packing Gland	Ductile Iron ASTM A536 (See Note 1)
7	Gland Bolts	316 Stainless Steel ASTM F593
8	Bonnet Bolts & Nuts	316 Stainless Steel ASTM F593 (bolt)/F594 (nut)
9	Stem Packing	Lubricated Flax
10	Guide Cap Bearings	Acetal
11	Wedge	(See Note 2)
12	Bonnet O-Ring	Nitrile ASTM D2000
13	Body	Ductile Iron ASTM A536 (See Note 1)
14	Stem	Manganese Bronze ASTM B138 (C67600) (See Note 3)
15**	Bonnet	Ductile Iron ASTM A536 (See Note 1)
16**	Yoke	Ductile Iron ASTM A536 (See Note 1)
17	O-Ring	Nitrile ASTM D2000
18	Disc Nut	Bronze ASTM B584
19	Stem Nut Pin	304 Stainless Steel


**2" – 6"/DN50 – DN150 Bonnet and Yoke are one piece.

Notes:

1. Material strength ASTM A536 65-45 minimum.
2. 2" – 12"/DN50 – DN300 Rubber Encapsulated Ductile Iron Wedge Rubber – SBR ASTM D2000.
3. Standard Stem is Manganese Bronze ASTM B138 (C67600). The R2361 is available as a PLUS version, with upgraded stem material etc. Please see PLUS version Datasheet.



MUELLER



DIMENSIONS - INCHES (MM)

VALVE SIZE	A-CLOSED	AA-OPEN	B	ØD	ØE	F	G	H	ØJ	NO. - ØK	ØL	# OF TURNS
2"/DN50	14.09 (357)	16.69 (424)	7.00 (178)	2.38 (60)	1.56 (40)	0.34 (9)	0.63 (16)	0.69 (18)	6.00 (153)	4 - .63 (16)	4.75 (121)	8.0
2½"/DN65	15.91 (404)	19.56 (497)	7.50 (191)	2.88 (73)	1.97 (50)	0.34 (9)	0.63 (16)	0.75 (19)	7.00 (178)	4 - .75 (19)	5.50 (140)	11.0
3"/DN80	15.66 (398)	19.31 (490)	8.00 (203)	3.50 (89)	2.63 (67)	0.34 (9)	0.63 (16)	0.81 (21)	7.50 (191)	4 - .75 (19)	6.00 (152)	11.0
4"/DN100	19.00 (483)	23.68 (601)	9.00 (229)	4.50 (114)	3.75 (95)	0.34 (9)	0.63 (16)	1.00 (25)	9.00 (229)	8 - .75 (19)	7.50 (191)	14.0
6"/DN150	24.50 (622)	31.38 (797)	10.50 (267)	6.63 (168)	5.80 (147)	0.34 (9)	0.63 (16)	1.06 (27)	11.25 (286)	8 - .88 (22)	9.50 (241)	20.5
8"/DN200	29.50 (749)	38.50 (978)	11.50 (292)	8.63 (219)	7.67 (195)	0.47 (12)	0.75 (19)	1.19 (30)	13.50 (343)	8 - .88 (22)	11.75 (298)	26.5
10"/DN250	35.75 (908)	47.00 (1194)	13.00 (330)	10.75 (273)	9.80 (249)	0.47 (12)	0.75 (19)	1.25 (32)	16.00 (406)	12 - 1.00 (25)	14.25 (362)	33.0
12"/DN300	40.50 (1028)	53.50 (1359)	14.00 (356)	12.75 (324)	11.80 (300)	0.47 (12)	0.75 (19)	1.31 (33)	19.00 (483)	12 - 1.00 (25)	17.00 (432)	38.5

WEIGHT - LB. (KG)

Valve Size	2"/DN50	2½"/DN65	3"/DN80	4"/DN100	6"/DN150	8"/DN200	10"/DN250	12"/DN300
Weight - Gr x Gr	37 (17)	44 (20)	45 (20)	74 (36)	118 (59)	189 (81)	285 (119)	372 (169)
Weight - Fl x Gr	41 (19)	50 (23)	52 (24)	86 (39)	134 (61)	212 (96)	316 (143)	427 (194)

OPTIONAL PLUGS

OPTION NO.	TAP SIZE
0008	½" (13 mm)
0054	¾" (19 mm)
0062	1" (25 mm)
0355	1¼" (32 mm)
0070	1½" (38 mm)
0366	2" (50 mm)

R-2361 OPTIONAL MAXIMUM TAP SIZE

Valve Size	2"/DN50	2½"/DN65	3"/DN80	4"/DN100	6"/DN150	8"/DN200	10"/DN250	12"/DN300
Max. Tap Size	¾" (19 mm)	½" (13 mm)	½" (13 mm)	¾" (19 mm)	1" (25 mm)	1¼" (32 mm)	1¼" (32 mm)	2" (50 mm)

For more information about us, or to view our full line of products, please visit www.mueller-international.com or call International Customer Service at:

UK: +44.1438.487410 Dubai: +971.4.214.6640 Singapore: +65.6816.3088 USA: +1.800.423.1323 | International@muellerwp.com

Mueller refers to one or more of Mueller Water Products, Inc., a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, Jones®, Krausz®, Mi.Net®, Milliken®, Pratt®, Pratt Industrial®, Singer®, and U.S. Pipe Valve & Hydrant. Please see muellerwp.com/brands to learn more.

© 2020 Mueller Water Products, Inc. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc., its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details visit www.muellerwp.com.