



MUELLER H-604 - MODEL 6

Operating Instructions

WARNINGS

- Should the equipment that the power operator is connected to suddenly stop turning or stall, the torque transmitted through the handle of the power operator may be sufficient to cause the person holding it to be thrown off balance. Before starting the power operator, the person operating should assume a stable, well braced, and balanced position on solid ground so this torque can be controlled. Do not use wire, tape, or any other means to hold the power operator switch or throttle in the “on” or “run” position. Doing so may prevent the power operator from shutting off in the event the person operating lets go of the handle.
- Lubrication unit has been shipped without lubricating fluid.

WHAT COMES IN THE BOX?

- Operator
- Oiler
- Extension
- Carrying case

AIR REQUIREMENTS

- Max air pressure 90 psi
- Min air pressure 50 psi
- *air pressure is measured at the inlet to the tool while the tool is spinning freely
- Minimum 65 SCFM

OILER

- Dixon Air King Universal Coupling connection
- Install oiler
- Adjust oil mist level between 5 and 30
- Type of oil to use: any petroleum-based, non-detergent light weight oil (SAE 10/150SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil, do not use any synthetic oil or oils containing additives or solvents
- Check fill level every 2-3 hours of operation

DIRECTION

- Reverse/forward
- Make sure direction lever is all the way to one position

EXHAUST

- Muffler can be rotated 360° to exhaust in any direction

MAINTENANCE

- Grease motor gears every 40 hours
- Use Top Cat grease 1100-826 or similar
- Use Top Cat grease gun 1100-824 or similar

TRIGGER

- Must release safety switch before operating the trigger

EXTENSION

- Can install extension between the handle and the motor for longer reaction arm



For more information about Mueller or to view our full line of water products, please visit www.muellerwp.com or call Mueller customer service at 1.800.423.1323.

Mueller refers to one or more of Mueller Water Products, Inc. (MWP), a Delaware corporation, and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. Mueller brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, HYMAX®, i20®, Jones®, Krausz® Mi.Net®, Milliken® Pratt®, Pratt Industrial®, Sentryx™, Singer®, and U.S. Pipe Valve & Hydrant. Please see muellerwp.com/brands to learn more.

© 2022 Mueller Co., LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Co., LLC., its affiliates or other third parties. Products marked with a section symbol (§) are subject to patents or patent applications. For details, visit www.mwppat.com. These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).