

CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

Issued to: MUELLER CO
500 W ELDORADO ST
PO BOX 671
DECATUR IL, 62525-1808 US

**This is to certify that
representative samples of**

DRINKING WATER SYSTEM COMPONENTS, DRINKING
WATER PRODUCTS AND MATERIALS CERTIFIED FOR
CANADA, LEAD CONTENT VERIFICATION OF
PRODUCTS IN CONTACT WITH POTABLE WATER

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: See Addendum page for Standards

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17


This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Standard(s) for Safety:

NSF/ANSI 61- Drinking Water System Components - Health Effects
NSF/ANSI 372- Drinking Water System Components – Lead Content
BNQ 3660-950 – Safety of Products and Materials in Contact with Drinking Water

PRODUCTS COVERED:

H-10022 ## ^^N	Eighth Bend Coupling, Swivel Nut with Female Mueller Coupling Thread x MIP, Sizes 5/8" thru 1"
H-10050 ## ^^N	Straight Coupling, Extra Strong (XS) Lead Flange Coupling x FIP, Sizes 1/2" x 3/4" thru 2"
H-10054 ## ^^N	Straight Coupling, Double Extra Strong (XXS) Lead Flange Coupling x FIP, Size 3/4"
H-15538 ## ^^N	Quarter Bend Coupling, MIP x MIP, Sizes 3/4" thru 2"
H-10094 ## ^^N	Straight Coupling, Swivel Nut with Female Increasing IP Thread x MIP, Size 3/4"
H-10096 ## ^^N	Quarter Bend Coupling, Female Increasing IP x MIP, Sizes 3/4" thru 2"***
H-10891 ## ^^N	Straight Meter Coupling, MIP x Meter Swivel Nut, Sizes 5/8" x 3/4" x 3/4" thru 2"
H-10892 ## ^^N	Quarter Bend Meter Coupling, Meter Swivel Nut x MIP, Sizes 5/8" x 1/2" thru 1"
H-12200 ## ^^N	Straight Coupling, Ribbed Connection for IPS PE Plastic Pipe x Female Copper Flare Thread (with clamp), Sizes 3/4" thru 1"***
H-12203 ## ^^N	Straight Coupling, Ribbed Connection for IPS PE Plastic Pipe x Female Copper Flare Thread, Sizes 3/4" thru 1"***
H-12210 ## ^^N	Straight Coupling, Ribbed Connection for IPS PE Plastic Pipe x MIP (with clamp), Sizes 3/4" thru 1"
H-12220 ## ^^N	Straight Coupling, Ribbed Connection for IPS PE Plastic Pipe x MIP (with clamp), Sizes 3/4" thru 1"
H-12213 ## ^^N	Straight Coupling, Ribbed Connection for IPS PE Plastic Pipe x MIP, Sizes 3/4" thru 1"



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

H-12215 ## ^^N	Straight Coupling, Ribbed Connection for IPS PE Plastic Pipe (with clamp), x FIP, Sizes 3/4" thru 1"
H-15471 ## ^^N	Eighth Bend Coupling, Swivel Nut with Female Increasing IP Thread x Copper Flare, Sizes 3/4" thru 1"
H-14200 ##^^N	Quarter Bend Meter Coupling, Meter Swivel Nut x Copper Flare, Size 5/8 x 3/4 thru 1"
H-10023 ## ^^N	Quarter Bend Coupling, Swivel Nut with Female Mueller Coupling Thread x MIP, Sizes 5/8" thru 1"
H-10076 ## ^^N	Eighth Bend Coupling, FIP x FIP, Size 3/4"
H-14211 ## ^^N	Quarter Bend Coupling, Lock Nut x FIP, Sizes 5/8" x 3/4" thru 1"
H-12221 ## ^^N	Straight Coupling, Ribbed Connection for IPS PE Plastic Pipe x Mueller 110 Compression Connection for CTS OD Tubing 3/4" thru 1"
H-10095 ## ^^N	Eighth Bend Coupling, FIP x MIP, Size 1-1/2" thru 2"
H-14232 ## ^^N	Straight Coupling, Compression Connection for Steel Pipe x FIP, Sizes 5/8" x 3/4" x 3/4"
H-14236 ## ^^N	Quarter Bend Coupling, Lock Nut x Copper Flare, w/ Test Valve, Size 5/8" x 3/4" thru 5/8" x 3/4" x 3/4"
H-14238 ## ^^N	Quarter Bend Coupling, Lock Nut x MIP, Size 5/8" x 3/4" thru 1"
H-15062 ## ^^N	Straight Coupling, Female Copper Flare Thread x Copper Flare, Sizes 3/4" x 1" thru 1" x 1-1/4"****
H-15063 ## ^^N	Eighth Bend Coupling, Female Copper Flare Thread x Copper Flare, Sizes 3/4" thru 2"****
H-15064 ## ^^N	Eighth Bend Coupling, Swivel Nut w/ Female Copper Flare Thread x Copper Flare, Sizes 3/4" thru 2"****
H-15068 ## ^^N	Quarter Bend Coupling, Female Copper Flare Thread x Copper Flare, Sizes 3/4" thru 2"****
H-15069 ## ^^N	Quarter Bend Coupling, Swivel Nut w/ Female Copper Flare Thread x Copper Flare, Sizes 3/4" thru - 2"****
H-15082 ## ^^N	Straight Coupling - Female Copper Flare Thread x FIP - Size 3/4" thru 2"****
H-15083 ## ^^N	Straight Coupling, Extra Strong (XS) Lead Flange x Female Copper Flare Thread, Size 3/4" x 1/2" thru 3/4"****

B. Mahlen

Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

H-1542310 ^^^N	Straight Coupling, Compression Connection w/ Set Screw for Steel Pipe x MIP, Sizes 3/4" thru 2"
H-14217 ## ^^^N	Straight Coupling, Lock Nut x Outside Thread for Mueller 5000 Series Meter Bar, Size 1"
H-15425 ## ^^^N	Straight Coupling, Female Copper Flare Thread x MIP, Sizes 1/2" thru 2"
H-15425 ## ^^^NJ	Straight Coupling, Female Copper Flare Thread x MIP, Sizes 1/2" thru 2"
H-14202 ## ^^^N	Quarter Bend Coupling, Lock Nut x Copper Flare, Size 5/8" x 3/4" thru 1"
H-14204 ## ^^^N	Quarter Bend Meter Coupling, Meter Flange x FIP, Size 1-1/2" thru 2"
H-14205 ## ^^^N	Straight Meter Coupling, Copper Flare x Meter Swivel Nut, Size 5/8" x 3/4"
H-14210 ## ^^^N	Quarter Bend Meter Coupling, Meter Swivel Nut x FIP, Size 5/8" x 3/4" thru 1"
H-14214 ## ^^^N	Quarter Bend Coupling, Lock Nut x FIP, Sizes 5/8" x 3/4" thru 1"
H-14215 ## ^^^N	Straight Meter Coupling, FIP x Meter Swivel Nut, Sizes 5/8 x 3/4" thru 1"
H-14216 ## ^^^N	Straight Coupling, Lock Nut x Copper Flare, Sizes 5/8 x 3/4" thru 5/8 x 3/4 x 3/4"
H-14219 ## ^^^N	Straight Coupling, Lock Nut x FIP, Sizes 5/8" x 3/4" thru 1"
H-14222 ## ^^^N	Straight Coupling, Multi-purpose thread x FIP, Sizes 5/8" x 3/4" thru 1"
H-14223 ## ^^^N	Straight Coupling, Multi-purpose thread x MIP, Sizes 5/8" x 3/4" thru 1"
H-15476 ## ^^^N	Quarter Bend Coupling, Swivel Nut with Female Increasing IP Thread x Copper Flare, Sizes 3/4" thru 1"
H-15485 ## ^^^N	Eighth Bend Coupling, Female Mueller Coupling Thread x Copper Flare, Sizes 1/2" x 3/4" thru 1"****
H-15490 ## ^^^N	Quarter Bend Coupling, Female Mueller Coupling Thread x Copper Flare, Sizes 1/2" x 3/4" thru 1"****
H-15506 ## ^^^N	Straight Union, Extra Strong (XS) Lead Flange Coupling x Copper Flare, Sizes 1/2" x 3/4" thru 3/4"
H-15513 ## ^^^N	Quarter Bend Coupling, Female Extra Strong (XS) Lead Flange Thread x Copper Flare, Sizes 1/2" x 3/4" thru 1"



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

H-15516 ## ^^N	Eighth Bend Coupling, Female Extra Strong (XS) Lead Flange Thread x Copper Flare, Sizes 5/8" x 3/4" thru 1"
H-15521 ## ^^N	Eighth Bend Coupling, Swivel Nut with Female Double Extra Strong (XXS) Lead Flange Thread x Copper Flare, Sizes 5/8" x 3/4" thru 3/4"
H-15427 ## ^^N	Straight Coupling, Multi-purpose thread x Sweat Joint Solder Connection, Sizes 5/8" x 3/4" x 3/4" thru 1"
H-15450 ## ^^N	Straight Coupling - Copper Flare x FIP - Sizes 1/2" thru 2"
H-15452 ## ^^N	Straight Coupling, IP Threaded Copper Flare Nut x FIP, Sizes 3/4" thru 1"
H-15455 ## ^^N	Eighth Bend Coupling, Copper Flare x FIP, Sizes 3/4" thru 1"
H-15460 ## ^^N	Quarter Bend Coupling, Copper Flare x FIP, Sizes 3/4" thru 2"
H-15465 ## ^^N	Straight Coupling, Female Increasing IP Thread x Copper Flare, Size 3/4" thru 2" x 1-1/2"
H-15467 ## ^^N	Straight Coupling, IP Threaded Copper Flare Nut x Female Increasing IP Thread, Size 3/4"
H-15470 ## ^^N	Eighth Bend Coupling, Female Increasing IP Thread x Copper Flare, Sizes 3/4" thru 2"
H-15475 ## ^^N	Quarter Bend Coupling, Female Increasing IP Thread x Copper Flare, Sizes 3/4" thru 2"
H-15480 ## ^^N	Straight Coupling, Female Mueller Coupling Thread x Copper Flare, Sizes 1/2" x 3/4" thru 1"
H-15486 ## ^^N	Eighth Bend Coupling, Swivel Nut with Female Mueller Coupling Thread x Copper Flare, Sizes 3/4" thru 1"
H-15510 ## ^^N	Straight Coupling, Female Double Extra Strong (XXS) Lead Flange Thread x Copper Flare, Sizes 5/8" x 3/4" thru 2"
H-15515 ## ^^N	Eighth Bend Coupling, Female Extra Strong (XS) Lead Flange Thread x Copper Flare, Sizes 5/8" x 3/4" thru 1"
H-15518 ## ^^N	Quarter Bend Coupling, Female Extra Strong (XS) Lead Flange Thread x Copper Flare, Sizes 5/8" x 3/4" thru 3/4"
H-15539 ## ^^N	Eighth Bend Coupling, MIP x Copper Flare, Sizes 3/4" thru 1"
H-14231 ## ^^N	Straight Coupling, Multi-purpose thread x Sweat Joint Solder Connection, Sizes 5/8" x 3/4" x 3/4" thru 1"



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

H-10879 ## ^^^N	Meter Bushing, Female Meter Spud Thread x Male Meter Spud Thread, 5/8" x 3/4" x 1" thru 3/4" x 1"
H-10889 ## ^^^N	Meter Bushing, Female Meter Spud Thread x Male Meter Spud Thread, 3/4" x 1"
H-10052 ## ^^^N	Straight Coupling, Extra Strong (XS) Lead Flange Coupling, Both ends, Size 5/8" thru 3/4"
47165N ^^^	Brass Bushing, MIP x FIP Thread, Size 1" x 3/4"
47169N ^^^	Brass Bushing, MIP x FIP Thread, Size 1-1/2" x 1"
H-10036 ^^^N	Brass Bushing, Male AWWA Taper (Mueller "CC") x Female AWWA Taper (Mueller "CC") Thread, Size 1" x 3/4" thru 2" x 1-1/2"
H-15491 ## ^^^N	Quarter Bend Coupling, Swivel Nut with Female Mueller Coupling Thread x Copper Flare, Sizes 3/4" thru 1"
H-10039 ^^^N	Brass Bushing, MIP x FIP Thread, Size 2" x 1-1/2"
47168N ^^^	Brass Bushing, MIP x FIP Thread, Size 1-1/2" x 3/4"
47172N ^^^	Brass Bushing, MIP x FIP Thread, Size 2" x 1-1/2"
H-14201 ## ^^^N	Straight Meter Coupling, Mueller 110 Conductive Compression Connection for CTS OD Tubing x Meter Swivel Nut, Size 5/8 x 3/4 x 3/4" thru 1"
H-14206 ## ^^^N	Quarter Bend Meter Coupling, Meter Swivel Nut x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Size 5/8 x 3/4 x 3/4" thru 1"
P-14206 ## ^^^N	Quarter Bend Meter Coupling, Meter Swivel Nut x Mueller Pack Joint Connection for CTS OD Tubing, Sizes 5/8" x 3/4" x 3/4" thru 1"
H-14207 ## ^^^N	Quarter Bend Coupling, Lock Nut x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Size 5/8" x 3/4" thru 1"
P-14207 ## ^^^N	Quarter Bend Coupling, Lock Nut x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Sizes 5/8" x 3/4" thru 1"
H-14208 ## ^^^N	Eighth Bend Meter Coupling, Meter Swivel Nut x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Size 5/8 x 3/4 x 3/4" thru 1"
P-14218 ## ^^^N	Straight Coupling, Lock Nut x Mueller Pack Joint Connection for CTS OD Tubing, Sizes 5/8" x 3/4" thru 5/8" x 3/4" x 3/4"



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

P-14237 ## ^^N	Quarter Bend Coupling, Lock Nut x Mueller Pack Joint Connection for CTS OD Tubing (with Test Valve), Sizes 5/8" x 3/4" thru 5/8" x 3/4" x 3/4"
H-14500 ## ^^N	Straight Meter Coupling, Mueller 110 Compression Connection for IPS PE Pipe x Meter Swivel Nut, Size 5/8" x 3/4" x 3/4"
H-15067 ## ^^N	Quarter Bend Coupling, Female Copper Flare Thread x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Size 3/4"-1"
P-15067 ## ^^N	Quarter Bend Coupling, Female Copper Flare Thread x Mueller Pack Joint Connection for CTS OD Tubing, Size 3/4"- 1"
H-15071 ## ^^N	Straight Coupling, Mueller 110 Conductive Compression Connection for CTS OD Tubing x Female Copper Flare Thread, Sizes 3/4" x 5/8" thru 2"****
E-15429 ## ^^N	Straight Coupling, Mueller Pack Joint Connection for IPS PE Pipe x MIP, Size 3/4" thru 2"
E-15454 ## ^^N	Straight Coupling, Mueller Pack Joint Connection for IPS PE Pipe x FIP, Size 3/4" thru 2"
H-15424 ## ^^N	Straight Coupling, Mueller Insta-tite Connection for CTS OD PE Tubing x MIP, Sizes 3/4" thru 1"
H-15426 ## ^^N	Straight Coupling, Mueller Insta-tite Connection for IPS PE Pipe x MIP, Sizes 3/4" thru 1"
P-15529 ## ^^N	Eighth Bend Coupling, Mueller Pack Joint Connection for CTS OD Tubing x MIP, Size 3/4" thru 1"
H-10127## ^^N	Mueller Meter Flange Service Fitting, Mueller 110 Compression Connection for CTS OD Tubing x Meter Flange, Sizes 1-1/2" thru 2"
P-15428 ## ^^N	Straight Coupling, Mueller Pack Joint Connection for CTS OD Tubing x MIP, Sizes 1/2" thru 2", 2" X 1 1/2", 1/2"x3/4", 1-1/4"x1-1/4", and 1"x2".
H-15428 ## ^^N	Straight Coupling - Mueller 110 Conductive Compression Connection for CTS OD Tubing x MIP - Sizes 1/2" thru 2"
P-14201 ## ^^N	Straight Meter Coupling, Mueller Pack Joint Connection for CTS OD Tubing x Meter Swivel Nut, Sizes 5/8" x 3/4" x 3/4" thru 1"
H-14218 ## ^^N	Straight Coupling, Lock Nut x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Sizes 5/8" x 3/4" thru 1"



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

H-15429 ## ^^N	Straight Coupling, Mueller 110 Compression Connection for IPS PE Pipe x MIP, Sizes 3/4" thru 1" x 3/4"
P-15451 ## ^^N	Straight Coupling, Mueller Pack Joint Connection for CTS OD Tubing x FIP, Sizes 1/2" thru 2 1/2" & 1 1/2" X 1 1/4"
H-15451 ## ^^N	Straight Coupling - Mueller 110 Conductive Compression Connection for CTS OD Tubing x FIP - Sizes 1/2" thru 2 1/2"
H-14237 ## ^^N	Quarter Bend Coupling, Lock Nut x Mueller 110 Conductive Compression Connection for CTS OD Tubing, w/ Test Valve, Size 5/8" x 3/4" thru 5/8" x 3/4" x 1"
H-15454 ## ^^N	Straight Coupling, Mueller 110 Conductive Compression Connection for IPS PE Pipe x FIP, Sizes 3/4" thru 1"
H-15456 ## ^^N	Straight Coupling, Mueller Insta-tite Connection for IPS PE Pipe x FIP, Sizes 3/4" thru 1"
H-15457 ## ^^N	Straight Coupling, Mueller Insta-tite Connection for CTS OD PE Tubing x FIP, Sizes 3/4" thru 1"
H-15481 ## ^^N	Straight Coupling, Mueller COupling Thread x 110 CTS, Size 3/4" thru 1"
P-15071 ## ^^N	Straight Coupling, Mueller Pack Joint Connection for CTS OD Tubing x Female Copper Flare, Size 3/4" thru 2****
H-15072 ## ^^N	Straight Coupling, Mueller 110 Conductive Compression Connection for IPS PE Pipe x Female Copper Flare Thread, Sizes 3/4" thru 1****
H-15074 ## ^^N	Straight Coupling, Mueller Insta-tite Connection for CTS OD PE Tubing x Female Copper Flare Thread, Sizes 3/4" thru 1****
H-15075 ## ^^N	Eighth Bend Coupling, Mueller 110 Conductive Compression Connection for CTS OD Tubing x Swivel Nut w/ Female Copper Flare Thread, Sizes 3/4" thru 2****
P-15075 ## ^^N	Eighth Bend Coupling, Mueller Pack Joint Connection for CTS OD Tubing x Swivel Nut with Female Copper Flare, Size 3/4" thru 1****
H-15076 ## ^^N	Quarter Bend Coupling, Mueller 110 Conductive Compression Connection for CTS OD Tubing x Swivel Nut w/ Female Copper Flare Thread, Sizes 3/4" thru 2****
P-15076 ## ^^N	Quarter Bend Coupling, Mueller Pack Joint Connection for CTS OD Tubing x Swivel Nut with Female Copper Flare, Size 3/4" thru 1****



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

H-15077 ## ^^N	Straight Coupling, Inside IPS PE Connection x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Size 1"
E-15072 ## ^^N	Straight Coupling, Mueller Pack Joint Connection for IPS PE Pipe x Female Copper Flare Thread, Size 3/4" thru 1-1/2"****
H-15487 ## ^^N	Eighth Bend Coupling, Mueller 110 Conductive Compression Connection for CTS OD Tubing x Swivel Nut with Female Copper Flare Thread, Sizes 3/4" thru 1"
P-15451 S ^^N	Straight Coupling, Mueller Pack Joint Connection for CTS OD Tubing x Solder
H-15529 ## ^^N	Eighth Bend Coupling, Mueller 110 Conductive Compression Connection for CTS OD Tubing x MIP, Sizes 3/4" thru 1"
P-15509 ## ^^N	Straight Coupling, Mueller Pack Joint Connection for CTS OD Tubing x Extra Strong (XS) Lead Flange Thread, Sizes 3/4" thru 1"
V-15102 ## ^^N	Straight Coupling, Swivel Nut with Female Copper Flare Thread x Mueller Pack Joint Connection for IPS PVC Pipe, Size 1"****
H-15512 ## ^^N	Straight Coupling, Mueller 110 Conductive Compression Connection for CTS OD Tubing x Double Extra Strong (XXS) Lead Flange Thread, Sizes 3/4" thru 1"
H-14220 ## ^^N	Straight COupling, Multi-purpose thread x Compression Connection for Steel Pipe, Sizes 5/8" x 3/4" x 3/4"
H-14227 ## ^^N	Straight Coupling, Multi-purpose thread x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Sizes 5/8" x 3/4" x 3/4" thru 1"
H-14229 ## ^^N	Straight Coupling, Multi-purpose thread x Mueller Insta-tite Connection for IPS PE Pipe, Sizes 5/8" x 3/4" x 3/4" thru 1"
H-15492 ## ^^N	Quarter Bend Coupling, Swivel Nut with Female Mueller Coupling Thread x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Sizes 3/4" thru 1"
H-15073 ## ^^N	Straight Coupling, Mueller Insta-tite Connection for IPS PE Pipe x Female Copper Flare Thread, Sizes 3/4" thru 1"
P-15531 ## ^^N	Quarter Bend Coupling, Mueller Pack Joint Connection for CTS OD Tubing x MIP, Sizes 3/4" thru 2"
H-15531 ## ^^N	Quarter Bend Coupling - Mueller 110 Conductive Compression Connection for CTS OD Tubing x MIP - Sizes 3/4" thru 2"



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

H-15533 ## ^^N	Quarter Bend Coupling, Mueller 110 Conductive Compression Connection for CTS OD Tubing x FIP, Sizes 3/4" thru 2"
P-15533 ## ^^N	Quarter Bend Coupling, Mueller Pack Joint Connection for CTS OD Tubing x FIP, Sizes 3/4" thru 2"
H-15534 ## ^^N	Eighth Bend Coupling, Mueller 110 Conductive Compression Connection for CTS OD Tubing x FIP, Sizes 3/4" thru 1"
P-15534 ## ^^N	Eighth Bend Coupling, Mueller Pack Joint Connection for CTS OD Tubing x FIP, Sizes 3/4" thru 1"
V-15440 ## ^^N	Straight Coupling, Mueller Pack Joint Connection for IPS PVC Pipe x MIP, Sizes 1" thru 2"
V-15442 ## ^^N	Straight Coupling, Mueller Pack Joint Connection for IPS PVC Pipe x FIP, Sizes 1" thru 2"
H-15413 ## ^^N	Straight Coupling, Swivel Nut with Female Mueller Coupling Thread x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Size 1"
H-15509 ## ^^N	Straight Coupling, Mueller 110 Conductive Compression Connection for CTS OD Tubing x Extra Strong (XS) Lead Flange Thread, Sizes 1/2" x 3/4" thru 1"
P-15422 ## ^^N	Straight Coupling, Mueller Pack Joint Connection for CTS OD Tubing x Male CC Thread, Size 1"
P-15512 ## ^^N	Straight Coupling, Mueller Pack Joint Connection for CTS OD Tubing x Double Extra Strong (XXS) Lead Flange Thread, Size 3/4"
E-14500 ## ^^N	Straight Meter Coupling, Mueller Pack Joint Connection for IPS PE Pipe x Meter Swivel Nut, Size 5/8" x 3/4" x 3/4"
E-14228 ## ^^N	Straight Coupling, Multi-Purpose Thread x Mueller Pack Joint Connection for IPS PE Pipe, Size 5/8" x 3/4" x 3/4"
H-14221 ## ^^N	Straight Coupling, Multi-purpose thread x Compression Connection with Set Screw for Steel Pipe, Sizes 5/8" x 3/4" x 3/4"
H-14228 ## ^^N	Straight Coupling, Multi-purpose thread x Mueller Compression Connection for IPS PE Pipe, Sizes 5/8" x 3/4" x 3/4" thru 1"
H-14230 ## ^^N	Straight Coupling, Multi-purpose thread x Mueller Insta-tite Connection for CTS OD Tubing, Sizes 5/8" x 3/4" x 3/4" thru 1"



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

P-14227 ## ^^N	Straight Coupling, Multipurpose Thread x Mueller Pack Joint Connection for CTS OD Tubing, Sizes 5/8 x 3/4" x 3/4" thru 1"
H-12948 ## ^^N	Straight Coupling, Mueller 110 Conductive Compression Connection for CTS OD Tubing x Extra Strong (XS) Lead Flange Coupling, Sizes 1/2" x 3/4" thru 3/4"***
E-14288 ## ^^N	Quarter Bend (90 degree) Coupling, Mueller 5000 Series Meter Bar Connection x Mueller Pack Joint Connection for PEP/PVC (IPS) Tubing, Size 5/8" x 3/4" x 3/4"
K-15071 ## ^^N	Straight Coupling, Kitec Connection x Female Copper Flare Thread, Size 3/4" x 5/8" thru 3/4"
K-15428 ## ^^N	Service Fitting, Kitec Connection x MIP Thread, Size 3/4" thru 1"
H-15098 ## ^^N	Straight Coupling, MIP x Female Copper Flair Thread, Size 3/4" thru 1"***
K-15451 ## ^^N	Straight Coupling, Mueller Kitec Connection x FIP, Size 3/4" thru 1"
H-15541## ^^N	Quarter Bend Coupling, FIP x FIP, Size 1" thru 2"
H-14234## ^^N	Expansion Handwheel 3 piece Unit, 4 spoke - Size 5/8" thru 1"
P-14208## ^^N	Eighth Bend Meter Coupling - Meter Swivel Nut x Mueller Pack Joint Connection for CTS OD Tubing - Size 5/8" x 3/4" x 3/4" thru 1"
682745N	Quarter Bend Coupling - Mueller Pack Joint Connection for IPS PE Pipe x FIP, Size 1"
682332N	Copper Flare Bushing conversion - To Convert Mueller 110 CTS connection to Copper Flare Connection - Size 3/4"
682333N	Copper Flare Bushing conversion - To Convert Mueller 110 CTS connection to Copper Flare Connection - Size 1"
538918E	Straight Coupling, MIP x Sweat Joint Solder Connection 1"
P-10127## ^^N	Mueller Meter Flange Service Fitting, Mueller Pack Joint Connection for CTS OD Tubing x Meter Flange, Size 1-1/2" thru 2"
H-15542## ^^N	Quarter Bend Coupling, FIP x MIP, Size 3/4" thru 2"
V-10120## ^^N	Mueller Meter Flange Service Fitting, Mueller Pack Joint Connection for IPS PVC Pipe x Meter Flange, Size 1-1/2" thru 2"
H-15458## ^^N	Straight Coupling, FIP x FIP, Size 2"



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

H-10129##* N	Water Meter Flange, Heavy style sizes 1-1/2" thru 2" Flange with FIP
H-10129##* N	Water Meter Flange, Standard style sizes 1-1/2" thru 2" Flange with FIP
H-10129##* N	Water Meter Flange, 1-1/2" Flange with MIP
G-15531## ^^N	Quarter Bend Coupling - Mueller Grip Compression Connection for CTS OD Tubing x MIP, Size 3/4" thru 2" [Annex G]
G-15533## ^^N	Quarter Bend Coupling - Mueller Grip Compression Connection for CTS OD Tubing x FIP, Size 3/4" thru 2" [Annex G]
G-15451## ^^N	Straight Coupling - Mueller Grip Compression Connection for CTS OD Tubing x FIP – Size 3/4" thru 2", 1-1/2"x1-1/4".
G-15428## ^^N	Straight Coupling - Mueller Grip Compression Connection for CTS OD Tubing x MIP – Size 3/4" thru 2", 1-1/2"x1-1/4".
G-14228 ## ^^N	Straight Coupling, Multi-Purpose Thread x Mueller Grip Compression Connection for IPS PE Pipe, Size 5/8" x 3/4" x 3/4`
G-15071## ^^N	Straight Coupling - Mueller Grip Compression Connection for CTS OD Tubing x Female Copper Flare Thread - Size 3/4" thru 2" [Annex G]
G-15076## ^^N	Quarter Bend Coupling - Mueller Grip Compression Connection for CTS OD Tubing x Swivel Nut with Female Copper Flare Thread - Size 1" thru 1 1/2" [Annex G]
G-14218## ^^N	Straight Coupling - Lock Nut x Mueller Grip Compression Connection for CTS OD Tubing - Size 5/8" x 3/4" thru 1" [Annex G]
H-15552## ^^N	Straight Coupling, Mueller 110 CTS Compression Connection x Mueller Pack Joint Connection for CTS OD Tubing, Size 1" x 3/4" [NSF372]
H-14209## ^^N	Eighth Bend Meter Coupling, Meter Swivel Nut x MIP, Size 5/8" x 3/4" x 3/4" [NSF 372]
P-14212## ^^N	Quarter Bend Meter Coupling, Meter Flange x CTS Pack Joint, Size 1-1/2" [NSF 372]
H-15482## ^^N	Straight Coupling, Female Mueller Coupling Thread x MIP, Size 1/2" x 3/4" [NSF 372]
H-15482## ^^N	Straight Coupling, Female Mueller Coupling Thread x MIP, Size 5/8" x 3/4" [NSF 372]
H-15483## ^^N	Straight Coupling, Female Mueller Coupling Thread x FIP, Size 1/2" x 3/4" [NSF 372]
H-15483## ^^N	Straight Coupling, Female Mueller Coupling Thread x FIP, Size 5/8" x 3/4" [NSF 372]



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

H-15397## ^^N	Service Tee, Solder Joint x FIP x Meter Swivel Nut connection, Size 3/4" [NSF 372]
H-15398## ^^N	Service Tee FIP x FIP x Meter Swivel Nut Connection, Size 3/4" [NSF 372]
H-15398## ^^N	Service Tee FIP x FIP x Meter Swivel Nut Connection, Size 1" [NSF 372]
G-15454## ^^N	Straight Coupling, Mueller Grip Connection for IPS PE Pipe x FIP, Size 3/4" [NSF 372]
G-15454## ^^N	Straight Coupling, Mueller Grip Connection for IPS PE Pipe x FIP, Size 1" [NSF 372]
G-15429## ^^N	Straight Coupling, Mueller Grip Connection for IPS PE Pipe x MIP, Size 3/4" [NSF 372]
G-15429## ^^N	Straight Coupling, Mueller Grip Connection for IPS PE Pipe x MIP, Size 1" [NSF 372]
G-15429## ^^N	Straight Coupling, Mueller Grip Connection for IPS PE Pipe x MIP, Size 1" x 3/4" [NSF 372]
H-15537## ^^N	Eighth Bend Coupling, MIP x MIP, Size 3/4" [NSF 372]
H-10038 ^^N	Brass Bushing, Male AWWA Taper (Mueller "CC") x MIP Thread, Size 2" x 1" [NSF 372]
H-10038 ^^N	Brass Bushing, Male AWWA Taper (Mueller "CC") x MIP Thread, Size 2" x 1-1/2" [NSF 372]
H-15507## ^^N	Straight Union, Female Extra Strong (XS) Lead Flange Coupling x FIP, Size 3/4" [NSF 372]
H-15511## ^^N	Straight Coupling, Female Double Extra Strong (XXS) Lead Flange Coupling x FIP, Size 3/4" [NSF 372]
K-15534## ^^N	Eighth Bend Coupling, Kitec Connection x FIP, Size 3/4" [NSF 372]
K-15534## ^^N	Eighth Bend Coupling, Kitec Connection x FIP, Size 1" [NSF 372]
P-15493## ^^N	Quarter Bend Coupling, Female Mueller Coupling Thread x Mueller Pack Joint Connection for CTS OD Tubing, Size 1/2" x 3/4" [NSF 372]
H-14213## ^^N	Straight Coupling - Inside British Straight Pipe Thread x Outside Meter Thread - Size 3/4" [NSF 372]
K-14227## ^^N	Straight Coupling, Multi-purpose thread x Kitec Connection for CTS OD Tubing, Size 5/8" x 3/4" x 3/4" [NSF 372]
G-15067## ^^NJ	Quarter Bend Coupling, Female Copper Flare Thread x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Size 3/4"-1"



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

G-15076## ^^^NJ	Quarter Bend Coupling - Mueller Grip Compression Connection for CTS OD Tubing x Swivel Nut with Female Copper Flare Thread - Size 1" thru 1 1/2" [Annex G]
G-1503##45^^^N	Straight Three Part Union, Extended Length - Mueller Grip Compression Connection for CTS OD Tubing 3/4" - 1"
P-1503##45^^^N	Straight Three Part Union, Extended Length - Mueller Pack Joint Connection for CTS OD Tubing Both Ends 3/4" - 1"
H-1503##45^^^N	Straight Three Part Union, Extended Length - Mueller 110 Conductive Compression Connection for CTS OD Tubing Both Ends 3/4" - 1"
G-15428##45^^^N	Straight Coupling, Extended Length - Mueller Grip Compression Connection for CTS OD Tubing x MIP 3/4" - 1"
P-15428##45^^^N	Straight Coupling, Extended Length - Mueller Pack Joint Connection for CTS OD Tubing x MIP 3/4" - 1"
P-12220## ^^^N	Straight Coupling, Ribbed Connection for IPS PE Plastic Pipe x Mueller Pack Joint Connection for CTS OD Tubing (with clamp) 3/4" thru 1"
P-12221## ^^^N	Straight Coupling, Ribbed Connection for IPS PE Plastic Pipe x Mueller Pack Joint Connection for CTS OD Tubing 3/4" thru 1"
H-15428##45^^^N	Straight Coupling, Extended Length - Mueller 110 Conductive Compression Connection for CTS OD Tubing x MIP 3/4" - 1"
H-15488## ^^^N	Eighth Bend Coupling, Swivel Nut with Female Mueller Coupling Thread x Mueller 110 Compression Connection for CTS OD Tubing 3/4"
H-15489## ^^^N	Quarter Bend Coupling, Swivel Nut with Female Mueller Coupling Thread x Mueller 110 Compression Connection for CTS OD Tubing 3/4"
H-14239## ^^^N	Straight Coupling, Compression Connection for Steel Pipe x MIP for Tapped Meter 1-1/2" - 2"
H-15423## ^^^N	Straight Coupling, MIP x Compression Connection for Steel Pipe 3/4" thru 2"



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

H-10128## ^^N	Mueller Meter Flange Service Fitting, Compression Connection for Steel Pipe x Meter Flange 1 1/2" thru 2"
H-15433## ^^N	Straight Coupling, Compression Connection for Steel Pipe, Both Ends 1 1/2" THRU 2"
H-15435## ^^N	Straight Coupling, Female Copper Flare Thread x Compression Connection for Steel Pipe
H-14501## ^^N	Straight Meter Coupling, Compression Connection for Steel Pipe x Meter Swivel Nut 5/8"x3/4"
M-15428## ^^N	Straight Coupling, Mueller MAX Wide Range Fitting x MIP- 3/4"thru 1"
M-15451## ^^N	Straight Coupling, Mueller MAX Wide Range Fitting x FIP- 3/4"thru 1"
H-10040## ^^N	Brass Bushing, MIP x Female AWWA Taper (Mueller "CC") Thread 3/4"x2" thru 2"x2"
E-15071## ^^N	Straight Coupling, Mueller Pack Joint Connection for IPS PE Pipe x Female Copper Flare Thread 3/4" x 1 thru 1"
H-15550## ^^N	Quarter Bend Coupling - Mueller 110 Conductive Compression Connection for CTS OD Tubing x PJ Swivel Connection, Size 3/4" thru 1"
H-15468## ^^N	Quarter Bend Coupling, Insta-Tite Compression Connection for CTS PE Pipe x FIP, Size 3/4" thru 1"
H-15473## ^^N	Quarter Bend Coupling, Insta-Tite Compression Connection for CTS PE Pipe x MIP, Size 3/4" thru 1"***
P-15492## ^^N	Quarter Bend Coupling, Swivel Nut w/ Female Mueller Coupling Thread x CTS Pack Joint, Size 3/4" thru 1"
H-15494## ^^N	Straight Service Fitting, Reducing Coupling, MIP x FIP, Size 2" x 1-1/2"
H-15551## ^^N	Quarter Bend Coupling - Mueller CTS 110/Pack Joint Swivel Connection x Copper Flare, Size 3/4" thru 1"



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number MH19738
Report Reference MH19738-20021210
Date 2021-December-17

K-15071## ^^N	Straight Coupling, Kitec Connection x Female Copper Flare Thread, Size 1"
H-14226## ^^N	Straight Coupling, Multi-Purpose Swivel Connection x Mueller 110 Conductive Compression Connection for CTS OD Tubing, Size 3/4" x 1"
H-10052## ^^N	Straight Coupling, Extra Strong (XS) Lead Flange Coupling, Both ends, Size 1/2"
H-14235## ^^N	Straight Meter Coupling, FIP x Multi-purpose Meter Swivel Nut, Size 3/4" x 1"
H-10888## ^^N	Meter Bushing, FIP x MIP, Size 5/8" x 3/4"
E-15071## ^^N	Straight Coupling, Mueller Pack Joint Connection for IPS PE Pipe x Female Copper Flare Thread, Size 3/4" x 1"
H-10031## ^^N	Brass Bushing, MIP x Female AWWA Taper (Mueller "CC") Thread, Size 1-1/4" x 1"
H-10879## ^^N	Water Meter Flange, Standard Style, Meter Swivel Nut x Flange Sizes, 1" x 1-1/2" thru 1" x 2"
H-10879## ^^N	Water Meter Flange, Standard Style, Flange x Flange, Sizes, 1" x 1-1/2" thru 1" x 2"

The above products were also evaluated to Standard BNQ 3660-950

*** The following Products are EXCLUDED from BNQ 3660-950 Certification

##= Any number from 00 through 99 representing specific product characteristics, or blank.


= R (Reduced Port), 1 (plain meter nut) or blank.

N = Alloy ASTM B584, C89520 or ASTM B584/B505, C89833

J = Designates "Jones" model marking

^^^ = Any 3 numbers that are representative of the product size.

-2 = Products designated with a "-2" are considered equivalent to products not bearing the "-2" designation



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>