

Albertville Plant 956 Industrial Blvd. Albertville, AL 35950 phone: 256-878-7930 fax: 256-891-6217 muellercompany.com

## Mueller Fire Hydrant Topcoat Touch-Up Kit Order Form

This form may be used to order materials to touch-up most coatings used on Mueller brand fire hydrants. Using this form places an order directly with Bluewater Supply, a distributor for Mankiewicz, the coating supplier - not with Mueller.

Mueller assumes no liability regarding the performance or suitability of these touch-up coatings.

### Please note the following:

- For the best results, follow the supplier's Mixing/Application Guide.
- Mueller does not guarantee an exact color match when using one of these kits to touch-up a factory applied coating.
- Use safety procedures and equipment as prescribed by your company and the paint suppliers while preparing surfaces, mixing, handling, and applying coatings.





## **Touch-up Kit Order Form**

Please call 252-638-3553 to place an order or email orders@bluewatersupply.com.

Because of the hazardous nature of these products we cannot offer any expedited shipping and freight will be in addition to the prices below.

SPRAY CANS			
MUELLER COLOR	MANKIEWICZ PART #	CASE (qty-6) PRICE	CASE QTY
Mueller Red 10	92977.31AQ.9.02D	\$118.74	
Mueller Yellow 14	92977.13F4.9.02D	\$118.74	
Mueller Safety Yellow M7	92977.13DP.9.02D	\$118.74	
Mueller White 15	92977.940Z.9.02D	\$118.74	
Other Color (Supply Part #)		\$118.74	

GALLON (Single Component)			
MUELLER COLOR	MANKIEWICZ PART #	GALLON PRICE	GALLON QTY
Mueller Red 10	96293.31AQ.9.373	\$68.00	
Mueller Yellow 14	96293.13F4.9.373	\$68.00	
Mueller Safety Yellow M7	96293.13DP.9.373	\$68.00	
Mueller White 15	96293.940Z.9.373	\$68.00	
Other Color (Supply Part #)		\$68.00	

QUART (Single Component)			
MUELLER COLOR	MANKIEWICZ PART #	QUART PRICE	QUART QTY
Mueller Red 10	96293.31AQ.9.509	\$24.00	
Mueller Yellow 14	96293.13F4.9.509	\$24.00	
Mueller Safety Yellow M7	96293.13DP.9.509	\$24.00	
Mueller White 15	96293.940Z.9.509	\$24.00	
Other Color (Supply Part #)		\$24.00	





Contact Name:	
Street Address:	
Street Address:	
City:	 State:
Country:	
Phone Number:	
Name on Card:	
Credit Card #:	
Expiration Date:	



# **Mixing/Application Guide**

	Base
Trade name	CELEROL ® 962.RQ

### Material:

1K solvent based topcoat

- For appearance only
- Touching up damaged surfaces

### Mixing:

Stir, high speed shear, or use a shaker until base material is homogenous

- Stirring: 5-7 minutes
- High speed shear: 2-3 minutes
- Shaker: 3-4 minutes

Material is ready to use after mixing is completed

### Application:

Clean the damaged areas with solvent to remove any dirt, oil or grease.

- Acetone, IPA, or MEK

Recommend scuffing/sanding damaged areas

- Remove high spots created by torn/ripped paint
- Better mechanical adhesion when scuffed

Clean sanded area with solvent to remove sanding dust

- Acetone, IPA, or MEK
- Allow ample time for solvent to evaporate
- Gently rub a tack rag across the sanded area to remove any leftover dirt/debris
- Recommended application methods
  - Spraying with a touch-up cup gun (Needle/Nozzle Size 1.0-1.2mm)
  - Dapping the material on with a brush (Recommend not brushing it on)

- Dabbing the paint enables a larger amount to be applied at once, helping with the leveling of the material.

-For best Results, please allow 24 hours to dry

